


5 Kg Carbon Dioxide Alloy Fire Extinguisher

Features

- ✓ Portable
- ✓ Class B & Electrical fires



A portable 5 Kg carbon dioxide alloy extinguisher for class B and electrical fires.




Specification

Extinguisher Code	CA5HH
Extinguishant	Carbon Dioxide CO ₂
Propellant Type	Stored Pressure
Capacity	5 Kg
Paint Primer/Finish	Polyester Powder Paint
Paint Colour	Signal Red (RAL 3000)
Colour Coding to BS7863	Black (RAL 9005)
Fire Class	B Type & Electrical
Fire Rating	70B
Operating Temperature	-20°C to +60°C
Test Pressure	250 Bar
Operating Pressure at 20°C	50 Bar
Discharge Duration	16 sec
Discharge Range	3 m
Cylinder	Aluminium Alloy
Operating Valve	Brass
Discharge Nozzle	Hose & Horn
Height	660 mm
Diameter	152 mm
Full Weight	11.6 kg
Nominal Carton Size	210 x 190 x 730 mm
Approval	BS EN3

Spare Parts

Item	Description	Part No.
A	Hose & Horn	MBC 030
B	Brass Parallel Valve	MVLV 0015
C	Safety Pin and Ring	MBC055
-	Pull Tight Seal (not shown)	XE 18798
-	Wall Bracket (not shown)	MBRH 0550



Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.